

PRATIKA 55 SMART T50

AUTOMATIC PACKAGING MACHINE - L-SEALING - INTEGRATED TUNNEL 50 DIGIT



DESCRIPTION

The PRATIKA 55 Smart T50 is an automatic shrink wrapping machine that stands out for its highly efficient tunnel, designed to significantly increase the production capacity. This tunnel is fully adjustable via PLC, allowing for precise and customized control of the packaging process. The machine is compact and optimized to deliver high performance, combining advanced technology



and ease of use.

What are the advantages of this new packaging machine?

- Brushless sealing bar servomotor
- Electric (non-pneumatic) feeding system
- Color touch screen control panel
- Compact (3.3 m²)
- Standard conveyor belt approach
- Vertical photocell for product detection included
- Single-chamber shrink tunnel 450x920x240 (LxPxH)
- Increased productivity

TECHNICAL FEATURES

Electrical supply	400V 50/60Hz 3Ph + inverter
Maximum installed power	9kW (400V)
Maximum electrical consumption	15A (400V)
Hourly production	0-1200 p/h
Maximum roll size	250x600 (ØxL)
Maximum product dimensions	400W 420L 120H
Conveyor belt height	870 mm (Standard on casters) Optional feet kit
Machine dimensions (Doors open)	2240x1625x2732 (WxLxH) mm
Machine dimensions (Doors closed)	1325x1625x2732 (WxLxH) mm
Machine packaging dimensions	1440x1990x2950 mm
Weight (Net/Gross)	730/865 kg



Machine color

RAL7035

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

TECHNICAL DRAWING

